



THREE POINT LINKAGE BOOMSPRAYS

AUSTRALIAN BUILT FOR TOUGH AUSTRALIAN CONDITIONS

The Hayes Spraying three point linkage boomspray is the proven sprayer of choice, having stood the test of time in the harshest of conditions.

The simple & robust construction includes self levelling boom, individual wing tilt & twin chain suspension as standard on all models.

Linkage boomsprays are available in two folding styles. Hydraulic folding booms take the effort out of folding and allows for greater manoeuvrability around obstacles with the in cab control panel. The manual folding boom offers a budget alternative with the boom folding effortlessly with pins & catches.

Improved productivity can be achieved when the linkage boomspray is used in conjunction with a tractor mounted front tank and twin tank plumbing.


The boomspray detaches easily from the tractor and is supported by adjustable park legs.

AVAILABLE FROM



Hayes Spraying
ABN 54 011 061 260
1 Troy Drive
PO Box 515
GOONDIWINDI QLD 4390

P 07 4671 3092
F 07 4671 3155
E sales@hayesspraying.com.au





THREE POINT LINKAGE BOOMSPRAYS

ROBUST & RELIABLE

The Hayes linkage range is built from dual grade steel ensuring strength and durability. The web truss design is suspended by twin chains which allows the boom to move slightly to cancel out stress on the boom & frame.

BOOM LENGTHS

Booms are available in lengths of 18m, 24m & 27m. Hydraulic folding booms include the antler frames for boom support during transport and are forward folding. Manual folding booms fold toward the back.



BOOM PLUMBING

Booms are standard with 3 section plumbing, 50cm nozzle spacing & one set of nozzles of choice.

Options include additional sections, 25cm nozzle spacings, second spray lines, fence line nozzles & triplex nozzle bodies (HF only).

PUMP & PLUMBING PACK

This system allows the linkage to be self contained. The hydraulic driven Hypro pump is located on the linkage with the filter system & clean water container.

TWIN TANK PLUMBING

The twin tank plumbing option is ideal for those wanting to increase their tank capacity & utilise their tractor mounted front tank & Hypro. The plumbing connects the linkage tank to the tractor mounted front tank system.

HYDRAULIC LEVELLING SYSTEM

The hydraulic levelling system is specially designed to provide improved ground following in contoured terrain when using hydraulic folding booms; resulting in reduced operator fatigue & a smoother boom ride. This option is only available when used with closed centre hydraulic tractors.

HEIGHT ADJUSTMENT

The height adjustment option allows for hydraulic folding booms to clear wheels on 3m tractors, dual wheeled tractors or wide tractor tyres. It also allows for greater crop clearance.



TANK SIZES

Hydraulic folding booms can be fitted with a 1200L, 1500L or 2000L tanks.

Manual folding booms can be fitted with a 1200L or 1500L tank.

FULLY DRAINABLE TANKS

The light coloured tanks allows for easy viewing of the tank level. The tanks are manufactured from UV stabilised polyethylene specifically formulated for chemical use. The smooth interior and integral sump enables complete decontamination & full drainage.

CONTROLLER INTERGRATION

Hayes adapter harness kits allow for common autoshutting controllers to be used.

